



## PINCURE Z 3W/CM<sup>2</sup> UV LED

**INNOVATIVE, HIGH POWERED  
UV LED PINNING**

Pincure Z UV LED offers a powerful solution in a compact and lightweight package for ultimate high speed pinning between inkjet print heads. The air cooling exhaust is from the top of the lamp head, away from any adjacent print heads.

The proven optics of the original Pincure model (which eliminates the risk of UV light damage to the print head nozzle plates) has been further enhanced, and in Pincure Z is now housed within a clever design which prohibits media contact and contamination to the lens.

The complete modular concept allows end to end mounting of 120mm and 80mm modules in every configuration to unlimited length. Up to 960mm (8 x 120mm Pincure Z heads) can be daisy-chained together with only one incoming electrical cable.

All of ITL's extensive UV LED product range have a life expectancy of 20,000 + operating hours as standard, ITL UV LED curing solutions are fitted with field replaceable modules offering extended service life and is covered by a comprehensive warranty backed by global support direct from Integration Technology and through its strategic partner IST Metz.

The Pincure system is also available in a watercooled Pincure C version.

For high speed applications requiring a higher peak intensity or greater dose, ITL offer a variety of final cure and more powerful Pinning UV-LED systems.

### Pincure Z Standard Features

Wavelength	395nm (Std), 365nm, 385nm, 405nm
Power	3 W/cm <sup>2</sup> *
Dimensions (LxWxH)	80mm/120mm x 20mm x 234mm
Emission window	80mm x 7mm, 120mm x 7mm
Operation Temperature	<40°C
Weight	80mm head: 400gms 120mm head: 550gms
Cooling	Aircooled with changeable fan filters
Cable	up to 15m supply cable (highflex), up to 8 heads can be daisy chained
Protocol	Standard I/O or serial bus
Addressability	40mm steps **
Options	Smart hub DC Powersupply

\* @395nm measured at the emitting window using an EIT Power Map UVV sensor

\*\* Addressability patented by European patent: EP1599340/ GB2399162, Cross licence with Lumen Dynamics Group Inc. U.S. Patent No. 6,683,421



## WE HAVE THE CURE

Integration Technology Ltd.  
Heyford Park | Upper Heyford | Oxfordshire | OX25 5HA, UK  
Tel.: +44 (0) 1869 233611 | Fax: +44 (0) 1869 233599  
E-Mail: mail@integrationtechnology.com

[www.IntegrationTechnology.com](http://www.IntegrationTechnology.com)

Integration Technology North America | [NorthAmerica@integrationtechnology.com](mailto:NorthAmerica@integrationtechnology.com)  
Integration Technology Latin America | [LAM@integrationtechnology.com](mailto:LAM@integrationtechnology.com)  
Integration Technology Korea | [Korea@integrationtechnology.com](mailto:Korea@integrationtechnology.com)  
Integration Technology Japan | [Japan@integrationtechnology.com](mailto:Japan@integrationtechnology.com)  
Integration Technology (China) Ltd. | [China@integrationtechnology.com](mailto:China@integrationtechnology.com)