



IST INTECH
UV LED CURING SPECIALISTS

TAILORED UV LED CURING SYSTEMS

C SERIES

SC

**HIGH OUTPUT
WATER COOLED
UV LED CURING**



C-SERIES SC WATER COOLED UV LED



POWER

20 W/cm²



WINDOW

23mm



WAVELENGTH

405nm, 395nm,
385nm, 365nm



DIMENSIONS

[X] x 75mm x 157mm



WEIGHT

1300g

- Solid output (non-pulse width modulated)
- Fully scalable in length
- Switch mode power supply unit which ensures world-wide compatibility
- Variable Power
- Addressable as standard, offering width switching or zone selection
- STEADYcool
- XT8 technology

The SC with its unbeatable dose and unmatched linearity of output can outperform other watercooled units of this type.

Stable and precise high output.

Slim and compact architecture.



- Field replaceable modules offering extended service life
- Available at wavelengths of 365nm, 385nm, 395nm, 405nm
- Drive electronics fully integrated within the lamp head

 **STEADYCOOL**

WATER COOLING

 **XT8 LED**

UV BOOSTER

For more information visit:
istintech.com/intech-product/sc-sf

**EXPERIENCE
THE DIFFERENCE
UV LED
EXPERTS**



IST INTECH
UV LED CURING SPECIALISTS

CONTACT US TODAY FOR MORE INFORMATION



+44 (0) 1869 233611



mail@istintech.com



www.istintech.com