



**IST INTECH**  
UV LED CURING SPECIALISTS

# TAILORED UV LED PINNING SYSTEMS

Z SERIES

## PincureZ

HIGH POWERED  
UV LED  
PINNING



### Z-SERIES PINCURE Z AIR COOLED UV LED



POWER

3W/cm<sup>2</sup>



WINDOW

80mm x 7mm



WAVELENGTH

405nm, 395nm,  
385nm, 365nm



DIMENSIONS

80mm x 20mm  
x 234mm



WEIGHT

400g

- Constant output (non-pulse width modulated)
- Focussed
- Fully scalable in length
- Innovative optical design
- Variable Power
- Addressable as standard, offering width switching or zone selection
- Air cooled with replaceable filters

The Pincure Z UV LED offers a powerful solution in a compact and lightweight package for ultimate high speed pinning between inkjet printheads.

**High powered UV LED pinning.**

**Compact and lightweight design.**



- Modular concept allows end-to-end mounting of 120mm and 80mm modules in every configuration to unlimited length
- Upto 960mm (8 x 120mm Pincure Z heads) can be daisy-chained together with only one incoming electrical cable
- Available at wavelengths of 365nm, 385nm, 395nm, 405nm



AIR COOLING



UV BOOSTER

For more information visit:  
[istintech.com/intech-product](http://istintech.com/intech-product)

EXPERIENCE  
THE DIFFERENCE  
UV LED  
EXPERTS



**IST INTECH**  
UV LED CURING SPECIALISTS

CONTACT US TODAY FOR MORE INFORMATION



+44 (0) 1869 233611



[mail@istintech.com](mailto:mail@istintech.com)



[www.istintech.com](http://www.istintech.com)